
П

Audi of America Inc., 2200 Ferdinand Porsche Dr., Herndon, Va. 20171; www.audiusa.com



SCALE: 10 IN. (254MM) DIVISIONS • DRAWINGS BY TIM BARKER

	Audi	BMW
	TTS	135i
		TA
List price	\$45,500	\$35,850
Price as tested	\$52,075	\$38,175
	Price as tested incl std equip. (ABS, dual front, side & knee air- bags, yaw & traction cntrl, Quat- tro awd, S tronic transmission, auto. climate cntrl, cruise cntrl, HID headlights, AM/FM/CD/AUX	Price as tested incl std equip. (ABS, dual front, side & curtain airbags, yaw & traction cntrl, moonroof, auto. climate cntrl, cruise cntrl, HID adaptive leveling & cornering headlights, AM/FM/
	audio), Premium Plus pkg (10- way adj heated seats, Bluetooth) \$2000, nav system (\$1950), Silk Nappa leather (\$1000), 19-in. wheels with summer tires (\$800), dest charge (\$825).	CD/AUX audio, multifunction steering wheel), Sport pkg (sport seats, M steering wheel, Shadow- line trim, top speed limiter raised) \$1100, iPod and USB adapter (\$400), dest charge (\$825).
Curb weight	3235 lb	3375 lb
Test weight	3405 lb	3545 lb
Weight dist (w/		
driver), f/r, %	62/38	54/46
Wheelbase	97.2 in.	104.7 in.
Track, f/r	61.2 in./61.4 in.	57.9 in./58.9 in.
Length Width	165.3 in.	172.2 in. 68.8 in.
***************************************	72.5 in. 53.1 in.	55.4 in.
Height	ווו ו.ככ.	ווו 4.ככ.
	ENGINE	
Туре	dohc 4-valve/cyl turbocharged I-4	dohc 4-valve/cyl twin-turbo- charged I-6
Displacement	1984 cc	2979 сс
Bore x stroke	82.5 x 92.8 mm	84.0 x 89.6 mm
Compression ratio	9.8:1	10.2:1
Horsepower (SAE)	265 bhp @ 6000 rpm	300 bhp @ 5800 rpm
Torque	258 lb-ft @ 2500–5000 rpm	300 lb-ft @ 1400–5000 rpm
Redline/limiter Fuel injection	6800/6800 rpm direct	7000/7000 rpm direct
Recfuel	premium	premium
Rectives		
	CHASSIS & BO	
Layout Body/frame	front engine/all-wheel drive unit steel & aluminum	front engine/rear drive unit steel
Brakes, front	13.4-in. vented discs/2-piston	13.3-in. vented discs/6-piston
	sliding calipers 12.2-in. vented discs/1-piston	fixed calipers
rear	sliding calipers; vac assist, ABS	
Wheels Tires	cast alloy; 19 x 9 Continental ContiSportContact3;	cast alloy; 18 x 7½ f, 18 x 8½ r
Tires	255/35ZR-19 96Y	215/40R-18 85Y f, 245/35R-18 88Y r
Steering	rack & pinion, elect. power assist	rack & pinion, elect. power assist
Steering ratio	16.9:1	15.3:1
Turns lock to lock	2.8	3.0
Suspension, f/r	MacPherson struts, coil springs, elect. adj tube shocks, anti-roll	MacPherson struts, coil springs, tube shocks, anti-roll bar/multi-
	bar/multilink, coil springs, elect. adj tube shocks, anti-roll bar	
	ACCOMMODATI	IONS
Seating capacity	2+2	2+2
Head room, f/r	38.0 in./32.0 in.	36.5 in./35.5 in.
Front-seat leg room	44.0 in.	44.3 in.
Rear-seat knee room	17.8 in.	22.0 in.
Trunk space	13.1 cu ft	10.0 cu ft



NITROGEN The Official Fuel Partner of Road & Track

200

Ш U


Z V Z V

<u>О</u>

ď Ш

П

BMW of North America, P.O. Box 1227, Westwood, N.J. 07675-1227; www.bmwusa.com



	Audi		BMW		
	TTS		135i		
ime to distance, secon		ERATI	ON		
	13.2 @ 105.2 mph	1	13.3 @ 105.3 mp	h	
130		Time to speed	Audi TTS	BMW 135i	
120		0-120 mph	18.3	17.2	
110		0-110 mph	14.8	14.5	
100	100	0-100 mph	11.8	11.7	
90		0-90 mph	9.6	9.7	
80		0-80 mph	7.6	8.0	
70		0-70 mph	6.0	6.5	
60 /		0-60 mph	4.6	4.7	
50		0-50 mph	3.5	3.7	
40		0-40 mph	2.5	2.4	
30		0-30 mph	1.7	1.6	
20 /		0-20 mph	1.0	1.0	
₇ 10		0-10 mph	0.5	0.3	
Σ 0 SEC 5	10 15 20	— O — = ¼ mil	le		
2 0320 3		AKING			
linimum stopping dist					
From 60 mph	115 ft		117 ft		
From 80 mph otal swept area	202 ft 209 ft 586 sq in. 597 sq in.				
wept area per ton	362 sq in.		354 sq in.		
	AAH	IDLING			
ateral accel *	0.98g		0.92g		
Balance			mild understeer	rsteer	
ilalom speed** Balance	72.0 mph 71.0 mph mild understeer mild understeer				
200-ft skidpad; ** 700		rina.	illiu uliuersteer		
	· · · · · · · · · · · · · · · · · · ·	ETRAII	N		
ransmission	6-speed paddle-sl		6-speed manual		
	Ratio/Overall/(Rpm) Mph				
lst,:l	2.92/13.93/(6800) 37		4.06/12.50/(7000) 41		
2nd,:1 3rd,:1	1.96/9.35/(6800) 54 1.40/6.68/(6800) 76		2.40/7.39/(7000) 69 1.58/4.87/(7000) 105		
4th,:1	1.03/4.91/(6800) 103		1.19/3.67/(7000) 140		
5th,:1	1.08/3.72/(6800) 137		1.00/3.08/est (6300) 150*		
6th,:1			0.87/2.68/est (5	500) 150*	
inal drive ratio ingine rpm @ 60 mph	4.77:1 (1st–4th), 3.44:1 (5th–6th) 3.08:1 2400 rnm 2200 rnm				
n top gear	2 100 i pili	2400 rpm 2200 rpm			
Electronically limited					
	FUEL E	CONO	MY		
Our driving	19.9 mpg		19.7 mpg		
PA city/highway ruise range			17/25 mpg 256 miles		
ruise range uel capacity	297 miles 15.9 gal.		14.0 gal.		
	INTERI	OK NU			
dle in neutral	45 dBA		51 dBA		
	45 dBA 79 dBA		51 dBA 76 dBA		
dle in neutral Maximum, 1st gear Constant 50 mph Constant 70 mph					

TEST CONDITIONS

calm

350 ft Location Irvine, California

37% **Wind**

Humidity